

Metro Combi

METRO

H 117 • 135

P 100

L 100 • 130 • 150

Pastry • Bakery • Hot snack • Food & Beverage

Installation

- Plug-in (multiplexable)
- Remote (multiplexable)

Configuration

Upper compartment 1 (to serve)
- Heated Top (Optional)
- Intermediate shelf (H135)
Lower compartment 2
(self service)

Temperature

- -1/+7 °C (TN)
- +65°C/+ 80°C (TC S)

Refrigerant

- R290 (Plug-in)
- R452A (Remote)

Refrigeration

- Ventilated
- Deactivation
(Upper compartment 1)

Compressor

Hermetic

Defrost

Off cycle

Climate class

3

Front glass

Low emission single

Side glasses

Double

Rear closing system

Polycarbonate sliding doors
(Upper compartment 1)

Opening system

Self-night curtain
(Lower compartment 2)

Lighting

- 3000 K
- 4000 K (Optional)
- 5700 K (Optional)

Base

- Height adjustable feet
- Swivel casters with brake
(Optional)

Color

White RAL 9003

Installazione

- Plug-in (canalizzabile)
- Remoto (canalizzabile)

Configurazione

Vano superiore 1 (servita)
- Piano Caldo (Optional)
- Mensola intermedia (H135)
Vano inferiore 2 (self service)

Temperatura

- -1/+7 °C (TN)
- +65°C/+ 80°C (TC S)

Refrigerante

- R290 (Plug-in)
- R452A (Remoto)

Refrigerazione

- Ventilata
- Disattivazione
(Vano superiore 1)

Compressore

Ermetico

Sbrinamento

Fermata compressore

Classe Climatica

3

Vetro frontale

Singolo bassoemissivo

Vetri laterali

Doppio (Camera)

Chiusura posteriore

Scorrevoli in policarbonato
(Vano superiore 1)

Apertura anteriore

Tenda notte manuale
(Vano inferiore 2)

Illuminazione

- 3000 K
- 4000 K (Optional)
- 5700 K (Optional)

Basamento

- Piedini regolabili in altezza
- Ruote pivotanti con freno
(Optional)

Colore

Bianco RAL 9003



R290

Upper	TN	TB	TB/TN	TC	TC/TN	N
Compartment 1	Chiller	Freezer	Dual Temp	Heated	Hot&Cold	Non-refrigerated
RS - Static						
RV - Ventilated	•					
RS/TC S - Static and Dry Heat convertible						
RV/TC S - Ventilated / Dry Heat convertible						
HUR - Meat						
CH - Chocolate						
TC S - Dry Heat				•		
TC BM - Bainmarie						
N - Non-refrigerated						•

Lower	TN	TB	TB/TN	TC	TC/TN	N
Compartment 2	Chiller	Freezer	Dual Temp	Heated	Hot&Cold	Non-refrigerated
RS - Static						
RV - Ventilated	•					
RS/TC S - Static and Dry Heat convertible						
RV/TC S - Ventilated / Dry Heat convertible						
HUR - Meat						
CH - Chocolate						
TC S - Dry Heat						
TC BM - Bainmarie						
N - Non-refrigerated						•



H 135



H 117

100	130	150
RV TN - TC S - N		



External dimensions (LxDxH) Dimensioni esterne (LxPxH)	H117	1000x1040 x1170/1216 mm	1300x1040 x1170/1216 mm	1500x1040 x1170/1216 mm
	H135	1000x1040 x1350/1397 mm	1300x1040 x1350/1397 mm	1500x1040 x1350/1397 mm
Capacity (gross/net) Capacità (lorda/netta)	H117	261 / 171 lt	348 / 228 lt	405 / 266 lt
	H135	334 / 171 lt	444 / 228 lt	518 / 266 lt
Net weight Peso netto	H117	240 kg	260 kg	275 kg
	H135	275 kg	275 kg	290 kg
Refrigeration Refrigerazione		Ventilated Ventilata		
Refrigerant Refrigerante		R290		
Climate class Classe climatica		3		
Operating conditions Condizioni ambientali		25 °C / 60 %RH		
Product temperature Temperatura prodotto	RV TN	-1 / +7 °C		
	TC S	+65 °C		
	N	-		
Compressor (q.ty - type) Compressore (q.tà - tipologia)		1 - Hermetic 1 - Ermetico		
Defrost Sbrinamento		Off Cycle Fermata compressore		
Power supply Alimentazione		230 V / 1 Ph / 50 Hz		
Electrical input (nominal) Assorbimento elettrico (regime)	RV TN - RV TN	890 W / 4 A	910 W / 4,1 A	1150 W / 4,7 A
	RV TN - TC S	1610 W / 6,3 A	1820 W / 7,1 A	2250 W / 8,8 A
	RV TN - N	890 W / 4 A	910 W / 4,1 A	1150 W / 4,7 A
Electrical input (defrost) Assorbimento elettrico (sbrinamento)	RV TN - RV TN	60 W / 0,3 A	60 W / 0,3 A	80 W / 0,4 A
	RV TN - TC S	780 W / 3 A	970 W / 3,8 A	1180 W / 4,6 A
	RV TN - N	60 W / 0,3 A	60 W / 0,3 A	80 W / 0,4 A

Technical sheet about models whit condensing unit included with air cooled
Dati tecnici riferiti a modelli con unità a bordo con condensazione ad aria

Setup
Allestimento

Shelf upper compartment 1 (LxD) Ripiano vano superiore 1 (LxP)	920 x 215 mm	1220 x 215 mm	1420 x 215 mm
Bottom upper compartment 1 (LxD) Ripiano di fondo vano superiore 1 (LxP)	910 x 602 mm	1210 x 602 mm	1410 x 602 mm
Bottom lower compartment 2 (LxD) Ripiano di fondo vano inferiore 2 (LxP)			

H117
P100
RV TN - RV TN



H135
P100
RV TN - RV TN

