Tornado TN-TB 1000 Power Unit

Gelato • Pasticceria
Gelato • Pastry

H 196
P 74
L 134

Installazione
Plug-in (free or built-in)

Configurazione
6 griglie regolabili in altezza

Temperatura di esercizio
-18 /-16 °C

Refrigerante
R290

Refrigerazione
Ventilata

Classe di prodotto
L1

Classe climatica
5

Compressore
Ermetico

Sbrinamento
Gas caldo

Vetro frontale
- Vetro camera riscaldato
- Film anti appannamento (optional)

Fianchi/Struttura
Coibentati in lamiera preverniciata bianca

Interno
Lamiera preverniciata bianca

Sistema di chiusura
- Porta a battente autochiudente
- Vetro camera riscaldato
- Film anti appannamento (optional)

Illuminazione
Led 5700 K

Movimentazione
Pattini unidirezionali con piedini regolabili in altezza

Installation
Plug-in (free or built-in)

Configuration
6 grids heigh adjustable

Temperature range
-18 /-16 °C

Refrigerant
R290

Refrigeration
Ventilated

Product class
L1

Climatic class
5

Compressor
Hermetic

Defrost
Hot gas

Front glass
- Heated double glass
- Anti fog film (optional)

Side panels/Structure
Insulated white prepainted sheet

Inside
White prepainted sheet

Closing system
- Self-clossing swing open door
- Heated double glass
- Anti fog film (optional)

Lighting
Led 5700 K

Equipment handling
Unidirectional runners with adjustable feet



Colori disponibili
Available colours

Interno Inside	**Esterno** Outside	**Fianchi** Side panels
Bianco White	Bianco White	Bianco White

POWER UNIT

Tornado 1000 Power Unit	**1000** TN RV	**1000** TB RV
Dimensioni esterne (LxPxH) External dimensions (LxDxH)	1340 x 740 x 1962 mm	
Peso (netto) Weight (net)	250 kg	
Refrigerazione Refrigeration	**Ventilata** Ventilated	
Refrigerante Refrigerant	R290	
Sbrinamento Defrost	**Fermata compressore** Off cycle	**Gas caldo** Hot gas
Temperatura prodotto Product temperature	-1/ +5 °C (TN)	-18/-16 °C (TB)
Classe climatica Climate class	5	
Condizioni ambientali Operating conditions	40 °C / 40% RH	
Classe energetica Energy class	A D G	

DATI ELETTRICI - Dati tecnici riferiti a modelli con unità a bordo ad aria R600a, illuminazione LED 5700K, chiusura con porta in vetro camera a battente autochiudente.
ELECTRICAL DATA - Technical sheet about models whit air-cooled plug-in unit R290, LED lighting 5700K, closing system self-clossing swing double glass door.

Compressore (q.tà - tipologia) Compressor (q.ty - type)	**1 Ermetico** 1 Hermetic	
Alimentazione Power supply	230 V / 1 Ph / 50 Hz	
Assorbimento elettrico (regime) Electrical input (nominal)	800 W / 4 A	1450 W / 8 A
Assorbimento elettrico (sbrinamento) Electrical input (defrost)	70 W / 0,3 A	1680 W / 8,8 A

ACCESSORI
OPTIONALS

Griglia plastificata con supporti (LxP) Plastified grid with supports (LxD)	470 x 585 mm	2x (530 x 475)
Vassoio fondo vasca (LxP) Bottom shelf (LxD)	470 x 585 mm	2x (530 x 475)

